



IR-67

Series Pocket IR Thermometers

300ms quickest sampling time with 1.5% accuracy (IR-65B)

Easy to use : hold it within two feet of the area to be measured and push the button

Large LCD screen shows readings in Fahrenheit or Celsius

Range: -35 to 250°C/-31 to 482°F (IR-65B)

Compact size design for the ultimate in convenience and portability

World smallest & IP rating 67 (IR-67/67B)



Features
User selectable °C or °F
Automatic Data Hold
Auto Power Off
Low battery indication
Lock function
Fast sampling time
Housing material


Size: 80mm x 40mmx25mm (IR-65/65B)

100mm x 25mm(IR-67/67B)

Weight: 36g (IR-65/65B) 33g(IR-67/67B)


Specifications	IR-67
Range	-35°C~230°C/ -31°F~446°F
Response Time	Less than 1 second
Basic Accuracy	±2% or ±2°C/±4°F
Optical Resolution	1:1
Emissivity	Fixed at 0.95
Resolution	0.1°C/°F

Applications




Series Pocket IR Thermometers


300ms quickest sampling time with 1.5% accuracy (IR-65B)
 Easy to use : hold it within two feet of the area to be measured and push the button
 Large LCD screen shows readings in Fahrenheit or Celsius
 Range: -35 to 250°C/-31 to 482°F (IR-65B)
 Compact size design for the ultimate in convenience and portability
 World smallest & IP rating 67 (IR-67/67B)



World smallest



>100°C Red backlit



≤100°C Green backlit

Accessories : One CR2032 button battery & Clamshell (IR-65/65B)

Two LR44(1.5V) button batteries, Clamshell (IR-67/67B)