

DT-125H/125G

Moisture Meters



125H/125G series moisture meters are used for testing moisture in wood, plaster and building materials. Integrated characteristics for 8 material groups increase the accuracy of measurements. The wet/dry indicator evaluates and interprets measurements with respect to the given material. The clearly organised, functional display and rubber guard around the housing make this unit well-suited for use in the rough professional environment.

125G can meet with different measuring requirements with various professional remote probes.



EMC
EN: 61326

Features

- Large LCD display
- Readings with Moisture Probe or Hammer Electrode
- Readings with Integral electrode Pins

Specifications

Model	125H	125G
Electrode length	8 mm	
Electrodes	Integrated, replaceable	
Measuring range Wood:	1 – 75 %	
Measuring range	Wood: 1 – 75 % Building material: 0.1– 2.4 % Ambient temperature: -40 to 70°C (-40 to 158°F) Ambient Relative Humidity: 0 to 100%	
Accuracy	Wood: 0...30% / ±1 % 30...60% / ±2% 60...75% / ±4% Other materials: / ±0.5%	
Ambient temperature	-40 °C~ -10°C and +40 ~ +70°C / ±2°C -10 °C~ +40°C / ±1°C	
Ambient Relative Humidity	0~20% and 80 ~ 100% /±5.0% 20~ 80%/±3.5%	
Auto power OFF	After approx. 3 minutes	
Auto LCD backlight OFF	After approx 10 seconds	
Housing material	Impact-proof plastic housing	
Ambient temperature	0 - 40°C	
Ambient Relative humidity	0 – 85 %RH	
Professional remote probes	No	Yes



Model 125G



Size(HxWxD): 160mm x 60mm x 28mm

Weight: 203g

Accessories :

3xCR2032 button batteries, Moisture Hammer Probe, Moisture Baseboard Probe, Moisture Probe Extenders, gift box and carrying case (125G)

3 x CR2032 button batteries (125H)