

DT-805/805L

Mini Sound Level Meter



EMC
EN: 50081-1, 50082-1
IEC61672-1

1.5dB Accuracy (805)

Level range: 30~130dB



805/805L Mini Sound level meter have a wide dynamic range from 30 to 130dB. They have different frequency weighting A and C to respond to human sense or machine monitoring purposes. For different sound pattern, they also supply Fast and Slow time constant setting.

Features

- Provides 1.5dB accuracy (805); Provides 2.0dB accuracy (805L)
- Meets IEC651 type 2 standards, IEC61672-1 Type 2 (805)
- Newly Design Shape
- High Performance
- Max Hold and Data Hold Function

Specifications

| | |
|---------------------|--|
| Level Range | Low = 30 ~ 100dB High = 60 ~ 130dB |
| Accuracy | ±1.5dB (ref 94dB @ 1kHz) |
| Frequency Range | 31.5Hz to 8kHz |
| Frequency Weighting | A, C |
| Time Weighting | Fast, Slow |
| Battery Type | 9V Battery NEDA 1604, IEC 6F22, JIS 006P |
| Operation Temp | 0°C~40°C(<80%R.H.) |
| Storage Temp | -10°C~60°C(<70%R.H.) |

Size(HxWxD): 210mm x 55mm x 32mm
Weight: 230g



Accessories :
9V battery, Carrying case and Gift box.