



CO-110 Carbon Monoxide Meter detects the presence of carbon monoxide (CO) and measures concentrations between 1-1000 parts per million (PPM). The Meter indicates the presence of CO by a reading on the LCD and a beeper tone. The beeper function much like clicking of a Geiger counter: Above 200 PPM, the beeper sounds continuously with the concentration of CO. From 35 PPM to 200 PPM, the beeper sounds discontinuously with the concentration of CO.

High Quality Sensor

- Memory for 10 complete data sets
- LED light & audible alarm



Features	
Digital LCD Display	
Auto/manual zero	
Memory for 10 complete data sets	
Record mode	
Red & Blue LED light audible alarm	
High Accuracy, quick response	
Pocket size and easy to use	
Fast sampling	
Max Hold	
Data Hold	
Above 200 PPM, the beeper sounds continuously	

Specifications	
Operating temperature	0°C to 50.0°C
Storage temperature	-30°C to 60.0°C
Operating humidity	0-90% relative humidity (non-condensing)
Measurement Range	0 to 1000PPM
Measurement Resolution	1PPM
Accuracy	±5% or ±10PPM
Warm up period	Less than 2 seconds
Battery	9V, NEDA 1604A or equivalent
Sensor type	Stabilized electrochemical Gas-specific (CO)
Typical sensor life	3 years

Size(HxWxD): 102mm x 52mm x 29mm
Weight: 84g



EMC
 EN: 50081-1, 50082-1



Accessories :

3.6V battery, Carrying case and Manual.