



660/661/662/663/663T Series are compact multimeters with high contrast 2000/4000 counts LCD display. They're all CAT III rated for 600V and provide 0.5% basic DCV accuracy.



EMC & LVD  
EN: 61326  
EN: 61010-1  
EN: 61010-02-032  
EN: 61010-02-033



**Safety Conformance**

- EN61010-1 CATIII 600V
- Full ranges protection

• 0.5% basic DC accuracy



Model 660



Model 661



Model 663T



Holster for option



**Features**

	660	661	662	663	663T
Digital display counts with Backlight	2000	2000	2000	4000	4000
Auto/manual ranging	manual	manual	Auto	Auto	Auto
True RMS measurements				*	*
Safety design	*	*	*	*	*
Data Hold	*	*	*	*	*
Auto Power Off			*	*	*
Type K temperature input					*

**Specifications**

Function	Max Range	Basic Accuracy	660	661	662	663	663T
Voltage DC	600V	±0.5%	*	*	*	*	*
Voltage AC	600V	±1.0%	*	*	*	*	*
Current DC	10A	±1.5%	*	*	*	*	*
Current AC	10A	±2.0%	*	*	*	*	*
Resistance	2MΩ	±1.0%	*	*			
	20MΩ				*		
	40MΩ				*	*	
Capacitance	4000μF	±3.0%				*	*
Frequency	10kHz	±1.0%				*	*
Duty Cycle	99.9%	±1.2%				*	*
Temperature	760°C/1400°F	±3.0%					*
Diode Check			*	*	*	*	*
Continuity Test			*	*	*	*	*
9V, 1.5V Battery Test			*				

**Size(HxWxD):** 120mm x 67mm x 46mm

**Weight:** 200g

**Accessories:**

Test leads, 1.5V AAA x 2 batteries, type K temperature probe (663T) and Clamshell.