


DT-930/931/932/931N/932N

6000 Counts Compact Digital Multimeters



930/931/932/931N/932N Series are compact meters with double molded plastic housing and over sized high contrast 6000 counts LCD display. They're all CAT III rated for 600V.

Safety Conformance

- EN61010-1 CATIII 600V, CATII 1000V
- Double molded plastic housing
- Full ranges protection

Features

	930	931/931N	932/932N
Digital display counts	6000	6000	6000
True RMS measurements			*
Analog bargraph/segments	61-segments	61-segments	61-segments
Safety design	*	*	*
Data Hold	*	*	*
MAX/MIN recording mode	*	*	*
Auto Ranging & Auto Power Off	*	*	*
Non-Contact ACV detection		931N	932N

Specifications

Function	Max Range	Basic Accuracy	930	931/931N	932/932N
Voltage DC	1000V	±0.5%	*	*	*
Voltage AC	1000V	±0.8%	*	*	*
Current DC	10A	±1.2%	*	*	*
Current AC	10A	±1.8%	*	*	*
Resistance	60MΩ	±0.8%	*	*	*
Capacitance	1000μF	±3.0%	*	*	*
Frequency	10MHz	±1.5%	*	*	*
Temperature	760°C/1400°F	±3.0%	*	*	*
Duty Cycle	9.99%	±1.2%	*	*	*
Diode Check			*	*	*
Continuity Test			*	*	*

Size(HxWxD): 150mm x 70mm x 48mm
Weight: 255g

Accessories:

Test leads, 9V battery, type K temperature probe (931/931N/932/932N) and gift box with carrying case.



EMC & LVD
 EN: 61326
 EN: 61010-1
 EN: 61010-02-032
 EN: 61010-02-033



Model 932N

- Double molded plastic housing
- Built-in Non-Contact AC Voltage Detector (931N/932N)

- True RMS (932/932N)
- 6000 counts LCD display



Model 932



Model 931

DT-940/941 Compact Digital Multimeters

Features

	940	941
Digital display counts	4000	4000
Data Hold & display backlight	*	*
Auto Ranging & Auto Power Off	*	*
1000V input protection on all ranges	*	*
Type K temperature input		*

Specifications

Function	Max Range	Basic Accuracy	940	941
Voltage DC	600V	±0.5%	*	*
Voltage AC	600V	±1.2%	*	*
Current DC	10A	±2.5%	*	*
Current AC	10A	±3.0%	*	*
Resistance	40MΩ	±0.8%	*	*
Capacitance	100μF	±3.0%	*	*
Frequency	10MHz	±1.5%	*	*
Temperature	760°C/1400°F	±3.0%	*	*
Duty Cycle	9.99%	±1.2%	*	*
Diode Check			*	*
Continuity Test			*	*

Size(HxWxD): 150mm x 70mm x 48mm
Weight: 255g

Accessories:

Test leads, 9V battery, Temperature Probe (941), carrying case and gift box.

940 Series are new compact multimeters with double molded plastic housing and over sized high contrast 4000 counts LCD display. They are all CAT III rated for 1000V.

Safety Conformance

- EN61010-1 CAT IV 600V, CAT III 1000V
- Double molded plastic housing
- 1000V input protection on all ranges
- 10A/600V fuse input protection on current ranges



EMC & LVD
 EN: 61326
 EN: 61010-1
 EN: 61010-02-032, EN: 61010-02-033



0.5% basic DCV accuracy



Model 940



Model 941