


DT-216/218/218T/219

CATIV 600V Pocket Multimeter with NCV Tester



- Double Molded housing
- CAT IV 600V
- Full range protection

- Non-Contact Voltage Detection
- Flashlight

The three pocket models 216, 218, 218T and 219 are double molded plastic housing and large high contrast 2000/4000 counts LCD display. They are all CAT IV 600V safety designed plus non-contact voltage detection & flashlight. 219 can measure 100A AC/DC current with 0.39" opening jaw .

Safety Conformance

- EN61010-1 CATIV 600V
- 200mA fused protection



Features

	216	218	218T	219
Digital display counts	2000	4000	4000	4000
Safety design	*	*	*	*
True RMS			*	*
Auto Ranging	*	*	*	*
Data Hold	*	*	*	*
Auto Power Off	*	*	*	*
Flashlight		*	*	*
Backlight	*	*	*	*
Non-Contact Voltage detection	*	*	*	*
Pocket size	*	*	*	*



- EMC & LVD
 EN: 61326
 EN: 61010-1
 EN: 61010-02-032
 EN: 61010-02-033



Model 218

Specifications

Function	Max Range	Basic Accuracy	216	218	218T	219
Voltage DC	600V	±0.5%	*	*	*	*
Voltage AC	600V	±1.0%	*	*	*	*
Current DC	100A	±2.5%	200mA	200mA	200mA	*
Current AC	100A	±3.0%	200mA	200mA	200mA	*
Resistance	20MΩ	±0.8%	*			
	40MΩ	±0.8%		*	*	*
Capacitance	4000uF	±3.0%		100uF	*	*
Frequency	10kHz	±(0.8%±5d)		*	*	*
NCV (VAC: 100V~600V)			*	*	*	*
Diode Check			*	*	*	*
Continuity Test			*	*	*	*

- 0.39" (10mm) Jaw opening (219)
- 100AAC/DC Current measurement (219)



Model 219

Size(HxWxD): 105mm x 60mm x 38mm

Weight: 145g

Accessories:

Test leads, two "AAA" batteries and clamshell.

