

DISSOLVED OXYGEN TRANSMITTER

Model : TR-DOT1A4

ISO-9001, CE, IEC1010



Lutron

LUTRON ELECTRONIC

The Art of Measurement

DISSOLVED OXYGEN TRANSMITTER

Model : TR-DOT1A4

Measure Range	<p><i>Range 1 :</i> O² CAL.</p> <p><i>Range 2 :</i> DO : 0 -20 mg/L</p>
Output	<p>4 - 20 mA</p> <p><i>Range 1 (CAL) :</i> 20.9 % O² = 12 mA</p> <p><i>Range 2 (DO) :</i> 0 mg/L = 4 mA 10 mg/L = 12 mA 20 mg/L = 20 mA</p>
External Adjustment	ZERO VR SPAN VR
Power Supply	90 - 260 ACV 50 Hz/60 Hz
Operation Temperature	0 - 50 °C 32 - 122 °F
Operation Humidity	Less than 80 %RH
Accessory Included	Dissolved Oxygen Probe Probe-filling electrolyte, OXEL-03 Spare diaphragms, OXDP-02
Optional Accessories	Probe-filling electrolyte, OXEL-03 Spare diaphragms, OXDP-02
Mounting	Din rail or Wall
Case	ABS plastic
Others	Separate probe with plug

* Appearance and specifications listed in this brochure are subject to change without notice.