



Specification

specification	Transmitter	Receiver
Weight	132.2g	59.2g
Size	64x31x119mm	48.6x26x177mm
battery	3.7V AAAx3lithium battery	6F22 9V battery
Signal Tracing Transmit Distance	>1km	
Display	2.0-inch TFT LCD	
Operating Temperature	-10 ~40°C (14 ~ 104°F)	
Operating Humidity	10-95%	
Storage Temperature	-20 ~ 60°C (-4~140°F)	

description

- A.socket RJ45
- B.socket RJ11
- C.TFT LCD
- D.protective cover
- E.charging hole
- F.scanning signal sensor
- G.flashlight
- H.operating indication LED
- I.earphone hole
- J.volume dial
- K.tracing scanning key
- L.flashlight on/off
- M.audio output
- N.battery door

Features

- (1)image display
- (2)audio output
- (3)wire tracing
- (4)charge and charging indication
- (5)low battery alarming
- (6)automatically turn off
- (7)flashlight function
- (8)earphone output
- (9)wire tracing sound level adjustable
- (10)2.0 inches TFT LCD
- (11)automatic PAL/NTSC identifying
- (12)12V 500m emergency power output, with short circuit protection
- (13)This device will turu off automatically within 8 minutes if there is no further operation of the key
- (14)1KMwire tracing distance: over 1 Km
- (15)3 built-in batteries of 3.7V 350mah
- (16)15V 1A power adaptor of 15V 1A

buttons

- (1) power indication LED
- (2) battery charge indication LED
- (3) foreign power LED indication
- (4) tracing scanning indication LED
- (5) on/off key
- (6) volume up
- (7) volume down
- (8) tracing key

