



Hoto Instruments EHT-600 Digital Tachometer / Lengthmeter

The EHT-600 tachometer features exceptional resolution at low speeds and statistics. It also features four measuring modes: Real time displays the current value, Maximum displays the highest value, Minimum displays the lowest value and Mean displays the average value taken during the test.



Call Us 800-832-0055

**For Information About Our
Trade In Program**

Manufacture: Hoto Instruments

SKU: **EHT-600**

Weight: 5.00 lb

**Free Ground Shipping within the 48
continental US States**

Please Call (800)832-0055

Features

The EHT-600 tachometer features exceptional resolution at low speeds and statistics. It also features four measuring modes: Real time displays the current value, Maximum displays the highest value, Minimum displays the lowest value and Mean displays the average value taken during the test. Its built with a ergonomic metal housing and operates on two standard AA batteries

- Rugged metal housing
- Ergonomic design fits comfortably in your hand and lessens fatigue
- Four measuring modes: Real time, maximum, minimum and mean
- Auto measuring range of 0 to 25,000 rpm with up to 0.01 rpm resolution up to 2,000 fpm using the optional 12" wheel
- 15 different measuring units: RPM, rev/sec, FPM, in/min, yd/min, in/sec, m/min, cm/min, cm/sec, revolutions, ft, in, yd, m, cm
- Last reading recall and 99 data memory
- Auto statistics: Max, Min and Mean
- Easy-to-read 5 digit 0.47" (12 mm) high LCD | Low battery indicator

Specifications

Specifications				
Model	EHT-600	EHT-601	EHT-602	EHT-603
Tach, cone & funnel adapters, carrying case	Included	Included	Included	Included

12" Wheel	-	-	Included	Included
4-AA rechargeable batteries & charger	-	Included	-	Included
Measuring Range	0.40 - 25000 RPM (floating decimal point) 0.40 - 2000.0 ft/min (w/12" wheel)			
Accuracy:	0.01% of reading ± 1 digit			
Display:	5 digit LCD 12mm Character Height			
Measuring Unit*	Speed Mode: RPM, rev/sec, FPM, in/min, yd/min, in/sec, m/min, cm/min, cm/sec Counter Mode: revolutions, ft, in, yd, m, cm			
Measuring Mode:	MEAN, MAX, MIN (speed measure mode)			
Memory:	Short Term Auto Memory: MAX, MIN, MEAN and last 9 data Long Term On-Demand memory: 99 data			
Display Update:	0.5 sec or 1.0 sec selectable			
Power:	2 - AA Battery, Approx. 80 hrs continuous operation			
Indicators:	LOW BATT, Units, MAX, MIN, MEAN and memory location			
Operating Temp:	0 - 45°C (32 - 113°F)			
Construction:	Die-cast aluminum housing			
Standard Accessories:	Cone adapter, funnel adapter, 2-AA Batteries, NIST traceable Certificate			
Optional Accessories:	12" wheel (surface speed measuring wheel is necessary to measure linear speed), 3-1/2" Extension Shaft			

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234

- © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.

