

Voltage measurement

*The L9438-53 is bundled

MAGNETIC ADAPTER 9804-01



Attaches to the tip of cord, red ×1, \varnothing 11 mm (0.43 in)

MAGNETIC ADAPTER 9804-02



Attaches to the tip of cord, black ×1, \varnothing 11 mm (0.43 in)

VOLTAGE CORD L9438-53



Black/ Red/ Yellow/ Blue, 3 m (9.84 ft) length, Alligator clip ×4

Storage media

* PC CARD 2G 9830, PC CARD 1G 9729 : cannot use with the 3169-20, 3169-21 * Supplied with PC Card adapter

PC Card Precaution

Use only PC Cards sold by HIOKI. Compatibility and performance are not guaranteed for PC cards made by other manufacturers. You may be unable to read from or save data to such cards.

PC CARD 512M 9728



- 512 MB capacity
- PC card adapter bundled

Printer options

RECORDING PAPER 1196



For the Printer 9442, 112 mm (4.41 in) × 25 m (82.03 ft), 10 rolls/set

PRINTER 9442



For printing numerical values 112 mm (4.41 in) paper width, not CE marked

AC ADAPTER 9443-02



For the Printer 9442, EU type

RS-232C CABLE 9721



Mini DIN 9pin to D-sub 9pin, straight, 1.5 m (4.92 ft) length

Other options

*The 9441 is bundled with the 3169-21

CONNECTION CABLE 9440



For external control, 2 m (6.56 ft) length

CONNECTION CABLE 9441



For D/A output, 2 m (6.56 ft) length

RS-232C CABLE 9612



For the PC, Mini DIN 9pin to D-sub 9pin, cross, 1.5 m (4.92ft) length

CARRYING CASE 9720-01



Soft type, Includes compartment for options, for the 3169 series