

## WT100-1/2/3 /1B Thermostatic Water Bath



**WT100-3**

### Feature

Ensure quality, service and development, the pursuit of excellence and persistence!

- 1、Unique and novel appearance, small size, powerful functions. All surface that contact with water adopt stainless steel material and PC material, with strong corrosion resistance.
- 2、Using a once punch-formed stainless steel inner liner, with unique sealing structure to eradicate water leakage; Three groups of water tanks postposition independent drain valves separately, can easily emptying the sewage after clean the inner container.
- 3、Using microcomputer program PID automatic temperature control, uniform temperature control, high precision.
- 4、Built-in water level sensor, to prevent the hidden dangers of dry burning, safe and reliable.
- 5、Dual digital tube digital holographic display temperature and timing time, parameter display is accurate and intuitionistic, with beep alarm prompt function.

### Parameters

Ensure quality, service and development, the pursuit of excellence and persistence!

Model	WT100-1	WT100-2	WT100-3	WT100-1B
Temp. range	RT.~100℃	RT.~100℃	RT.~100℃	RT.~100℃
Temp. accuracy	0.3℃	0.3℃	0.3℃	0.3℃
Temp. fluctuation	0.5℃	0.5℃	0.5℃	0.5℃
Temp. Uniformity@37℃	0.5℃	0.5℃	0.5℃	0.5℃
Number of holes	1	2	3	1
Volume	2L×1	2L×2	2L×3	5L×1
Inner dimension	135mm×150mm×143mm×1	135mm×150mm×143mm×2	135mm×150mm×143mm×3	325mm×150mm×176mm×1
Voltage	AC 220V 50/60Hz	AC 220V 50/60Hz	AC 220V 50/60Hz	AC 220V 50Hz
Power	800W	800W	800W	1000W
Dimensions	198mm×310mm×255mm	363mm×310mm×255mm	510mm×310mm×255mm	360mm×284mm×265mm
Net weight	2.3kgs	5.1kgs	6.7kgs	5.1kgs