

HI3846-0 - Chromium Reagent

Safety data sheet according to Regulation (EC) No. 1907/2006

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code. Product name. HI3846-0 Chromium Reagent

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use.

Determination of Hexavalent Chromium in Water Samples.

1.3. Details of the supplier of the safety data sheet.

Name. Full address.	Hanna Instruments S.R.L. str. Hanna Nr 1
District and Country.	457260 loc. Nusfalau (Salaj) Romania
	Tel. (+40) 260607700
	Fax. (+40) 260607700
e-mail address of the competent person. responsible for the Safety Data Sheet.	msds@hanna.ro
1.4. Emergency telephone number.	
For urgent inquiries refer to.	Emergency Number - International: +(1)-703-527-3887 - UK, London:

or argent inquines refer to:	
	+(44)-870-8200418 - CHEMTREC 24 hours/365 days

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Acute toxicity, category 3	H331	Toxic if inhaled.
Skin corrosion, category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Hazardous to the aquatic environment, chronic toxicity,	H412	Harmful to aquatic life with long lasting effects.
category 3		

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal	words:	

Danger

Hazard statements:	
H331	Toxic if inhaled.
H314	Causes severe skin burns and eye damage.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements: P260

Do not breathe dust, fume, gas, mist, vapours, spray.



Hanna Instruments S.R.L.

HI3846-0 - Chromium Reagent

Revision nr.1 Dated 10/10/2016 Printed on 16/11/2016 Page n. 2 / 10

SECTION 2. Hazards identification. .../>>

P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do
	Continue rinsing.
P310	Immediately call a POISON CENTER or doctor.
P404	Store in a closed container.

Contains: POTASSIUM DISULFATE

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identifica	ation.	x = Conc. %.	Classification 1272/2008 (CLP).
POTASS	IUM DISULFA	TE	
CAS.	7790-62-7	50 ≤ x < 100	Acute Tox. 3 H331, Skin Corr. 1A H314
EC.	232-216-8		
INDEX.			
SULPHA	MIC ACID		
CAS.	5329-14-6	30 ≤ x < 50	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Aquatic Chronic 3 H412
EC.	226-218-8		
INDEX.	016-026-00-0)	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown. For symptoms and effects caused by the contained substances, see chap. 11.

POTASSIUM DISULFATE Irritation and corrosion, Cough, Shortness of breath. Risk of blindness!. SULPHAMIC ACID Irritant effects, Cough, Shortness of breath, Pain, shock.

4.3. Indication of any immediate medical attention and special treatment needed. Information not available.



Hanna Instruments S.R.L.

HI3846-0 - Chromium Reagent

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

POTASSIUM DISULFATE

Not combustible. Ambient fire may liberate hazardous vapours. Fire may cause evolution of: Sulphur oxides.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.1A

6.3. Methods and material for containment and cleaning up.

Collect the leaked product and place it in containers for recovery or disposal. If the product is flammable, use explosion-proof equipment. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):

7.3.	Specific	end	use(s).
------	----------	-----	---------

Information not available.



SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Normal value in fresh	water					0,68	mg/l	
						,		
Normal value in mari		P				0,068	mg/l	
Normal value for fres						2,5	mg/kg/	
Normal value for mar						0,25	dhg/kg/	
Normal value for wat	er, intermitte	ent release				6,8	¢hg/l	
Normal value of STP	microorgan	nisms				800	mg/l	
Normal value for the	terrestrial c	ompartment				0,092	mg/kg/	
alth - Derived no-effe	ect level - C	DNEL / DMEL					d	
	Effects of	n consumers.			Effects on w	orkers		
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chroni c local	Chronic systemic
Inhalation.							0,13 mg/m3	0,13 mg/m3

Normal value in fresh	n water					1,8	mg/l	
Normal value in mari	ne water					0,18	mg/l	
Normal value for fres	h water sec	liment				8,36	mg/kg/	
Normal value for man	rine water s	ediment				0,84	dhg/kg∕	
Normal value for wat	er, intermitt	ent release				0,48	¢hg/l	
Normal value of STP	microorgar	nisms				20	mg/l	
Normal value for the	terrestrial c	ompartment				5	mg/kg/	
ealth - Derived no-eff	ect level - C	ONEL / DMEL					d	
	Effects o	n consumers.			Effects on w	orkers		
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chroni c local	Chronic systemic
Oral.			VND	5 mg/kg bw/d				
Inhalation.			VND	17,4 mg/m3			VND	70,5 mg/m3
Skin.			VND	5			VND	10
				mg/kg bw/d				mg/kg
								bw/d

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

Use a type P filtering facemask (see standard EN 149) or equivalent device, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.



SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical pr	roperties.
Appearance	solid powder
Colour	white
Odour	odourless
Odour threshold.	Not available.
pH.	1.2 - 1.5 pH, 15 g/L
Melting point / freezing point.	Not available.
Initial boiling point.	Not applicable.
Boiling range.	Not available.
Flash point.	Not applicable.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	2,300
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.
9.2. Other information.	
Total solids (250°C / 482°F)	100,00 %
VOC (Directive 2010/75/EC) :	0
VOC (volatile carbon) :	0

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

SULPHAMIC ACID Decomposes at 205°C/401°F.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The powders are potentially explosive when mixed with air.

SULPHAMIC ACID Risk of explosion on contact with chlorine. Reacts dangerously with metal nitrites and nitrates.

10.4. Conditions to avoid.

Avoid environmental dust build-up.

POTASSIUM DISULFATE Exposure to moisture.

10.5. Incompatible materials.

SULPHAMIC ACID Chlorine, nitric acid, sodium nitrites and nitrates, potassium.



SECTION 10. Stability and reactivity. ... />>

10.6. Hazardous decomposition products.

SULPHAMIC ACID Sulphur oxides and nitric oxides.

SECTION 11. Toxicological information.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects.

POTASSIUM DISULFATE

Acute inhalation toxicity, absorption, Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages, damage of respiratory tract, Lung oedema, Symptoms may be delayed - Skin irritation (in analogy to similar products), Causes severe burns. - Eye irritation (in analogy to similar products), Causes serious eye damage. Risk of blindness!.

SULPHAMIC ACID

Acute oral toxicity, Symptoms: Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract., Pain, Possible damages:, shock - Acute inhalation toxicity, Symptoms: Cough, Shortness of breath, Irritation symptoms in the respiratory tract - Skin irritation, Result: Irritations, Causes skin irritation - Eye irritation, rabbit, Result: Severe irritations, Causes serious eye irritation.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture: LC50 (Inhalation - mists / powders) of the mixture: LD50 (Oral) of the mixture: LD50 (Dermal) of the mixture:

POTASSIUM DISULFATE LD50 (Oral). LC50 (Inhalation).

SULPHAMIC ACID LD50 (Oral). LD50 (Dermal).

SKIN CORROSION / IRRITATION. Corrosive for the skin.

SERIOUS EYE DAMAGE / IRRITATION. Causes serious eye damage.

RESPIRATORY OR SKIN SENSITISATION. Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY. Does not meet the classification criteria for this hazard class.

CARCINOGENICITY. Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY. Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE. Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE. Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class.

Not classified (no significant component). 0,850 mg/l Not classified (no significant component). Not classified (no significant component).

2140 mg/kg Rat 0,85 mg/l/4h Rat

1050 mg/kg Guinea pig > 2000 mg/kg Rat



Hanna Instruments S.R.L.

Revision nr.1 Dated 10/10/2016 Printed on 16/11/2016 Page n. 7 / 10 ΕN

HI3846-0 - Chromium Reagent

SECTION 12. Ecological information.

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity.	
POTASSIUM DISULFATE LC50 - for Fish. EC50 - for Crustacea.	680 mg/l/96h Pimephales promelas 720 mg/l/48h Daphnia magna
SULPHAMIC ACID LC50 - for Fish.	70,3 mg/l/96h Pimephales promelas
12.2. Persistence and degradability.	
SULPHAMIC ACID Solubility in water. Biodegradability: Information not available.	> 10000 mg/l
12.3. Bioaccumulative potential.	
SULPHAMIC ACID Partition coefficient: n-octanol/water.	0,1 Log Kow
12.4. Mobility in soil. Information not available.	
12.5. Results of PBT and vPvB assessment.	
On the basis of available data, the product does no	ot contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

SULPHAMIC ACID

Biological effects: Harmful effect due to pH shift. Further information on ecology, Discharge into the environment must be avoided.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, IATA: 2923

14.2. UN proper shipping name.

ADR / RID:	CORROSIVE SOLID, TOXIC, N.O.S. (POTASSIUM DISULFATE) MIXTURE
IMDG:	CORROSIVE SOLID, TOXIC, N.O.S. (POTASSIUM DISULFATE) MIXTURE
IATA:	CORROSIVE SOLID, TOXIC, N.O.S. (POTASSIUM DISULFATE) MIXTURE



Revision nr.1 Dated 10/10/2016 Printed on 16/11/2016 Page n. 8 / 10

SECTION 14. Transport information. />>

14.3. Transport hazard class(es).

ADR / RID:	Class: 8	Label: 8 (6.1)	Ć
IMDG:	Class: 8	Label: 8 (6.1)	
IATA:	Class: 8	Label: 8 (6.1)	



14.4. Packing group.

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards.

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user.

ADR / RID:	HIN - Kemler: 86	Limited Quantities: 1 kg	Tunnel restriction code: (E)
	Special Provision: -		
IMDG:	EMS: F-A, S-B	Limited Quantities: 1 kg	
IATA:	Cargo:	Maximum quantity: 50 Kg	Packaging instructions: 863
	Pass.:	Maximum quantity: 15 Kg	Packaging instructions: 859
	Special Instructions:	A3, A803	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC:

H2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006. None.

Substances in Candidate List (Art. 59 REACH). On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None.

Substances subject to the Rotterdam Convention: None.

Substances subject to the Stockholm Convention: None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.



Revision nr.1 Dated 10/10/2016 Printed on 16/11/2016 Page n. 9 / 10

SECTION 15. Regulatory information. .../>>

WGK 2: Hazard to waters

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 3	Acute toxicity, category 3
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic toxicity, category 4
H331	Toxic if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).
- GENERAL BIBLIOGRAPHY
- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament

@EPY 9.2.8 - SDS 1003

ΕN



Revision nr.1 Dated 10/10/2016 Printed on 16/11/2016 Page n. 10 / 10

SECTION 16. Other information. ... / >>

- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: 14.