

HI7040-1 - Zero Oxygen Solution, Component I

Revision nr.1 Dated 27/10/2016 Printed on 03/11/2016 Page n. 1 / 9

# Safety data sheet according to Regulation (EC) No. 1907/2006

# SECTION 1. Identification of the substance/mixture and of the company/undertaking.

# 1.1. Product identifier.

Code. **HI7040-1** 

Product name. Zero Oxygen Solution, Component I

Chemical name and synonym. SODIUM METABISULFITE

 INDEX number.
 016-063-00-2

 EC number.
 231-673-0

 CAS number.
 7681-57-4

 Registration Number.
 01-2119531326-45

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use. Calibration of Dissolved Oxygen Probes.

## 1.3. Details of the supplier of the safety data sheet.

Name. Hanna Instruments S.R.L.

Full address. str. Hanna Nr 1

District and Country. 457260 loc. Nusfalau (Salaj)

Romania

Tel. (+40) 260607700 Fax. (+40) 260607700

e-mail address of the competent person.

responsible for the Safety Data Sheet. msds@hanna.ro

1.4. Emergency telephone number.

For urgent inquiries refer to. Emergency Number - International: +(1)-703-527-3887 - UK, London:

+(44)-870-8200418 - CHEMTREC 24 hours/365 days

# SECTION 2. Hazards identification.

# 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Acute toxicity, category 4 H302 Harmful if swallowed.
Serious eye damage, category 1 H318 Causes serious eye damage.

## 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Danger

Hazard statements:

H302 Harmful if swallowed.
H318 Causes serious eye damage.
EUH031 Contact with acids liberates toxic gas.

ΕN



# Hanna Instruments S.R.L.

# HI7040-1 - Zero Oxygen Solution, Component I

Revision nr.1 Dated 27/10/2016 Printed on 03/11/2016 Page n. 2 / 9

SECTION 2. Hazards identification. .../>>

Precautionary statements:

**P280** Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P310 Immediately call a POISON CENTER or doctor.

Contains: SODIUM METABISULFITE

INDEX. 016-063-00-2

### 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

# **SECTION 3. Composition/information on ingredients.**

## 3.1. Substances.

Contains:

Identification. x = Conc. %. Classification 1272/2008 (CLP).

**SODIUM METABISULFITE** 

CAS. 7681-57-4 100 Acute Tox. 4 H302, Eye Dam. 1 H318, EUH031

EC. 231-673-0 INDEX. 016-063-00-2 Reg. no. 01-2119531326-45

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## 3.2. Mixtures.

Information not relevant.

## **SECTION 4. First aid measures.**

## 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

SODIUM METABISULFITE

Irritation and corrosion. Risk of serious damage to eyes.

## 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

# **SECTION 5. Firefighting measures.**

## 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide and chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water.

Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.



HI7040-1 - Zero Oxygen Solution, Component I

Revision nr.1 Dated 27/10/2016 Printed on 03/11/2016 Page n. 3 / 9

SECTION 5. Firefighting measures. />>

### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If large quantities of the product are involved in a fire, they can make it considerably worse. Do not breathe combustion products.

#### SODIUM METABISULFITE

Not combustible. Ambient fire may liberate hazardous vapours. Fire may cause evolution of: Sulphur oxides.

#### 5.3. Advice for firefighters.

**GENERAL INFORMATION** 

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire, if it is safe to do so.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

# 6.3. Methods and material for containment and cleaning up.

Collect the leaked product and place it in containers for recovery or disposal. If the product is flammable, use explosion-proof equipment. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

## 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage.**

## 7.1. Precautions for safe handling.

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment

## 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

## 7.3. Specific end use(s).

Information not available.

# **SECTION 8. Exposure controls/personal protection.**

# 8.1. Control parameters.

Regulatory References:

ESP España INSHT - Límites de exposición profesional para agentes químicos en España 2015

FRA France JORF n°0109 du 10 mai 2012 page 8773 texte n° 102

GBR United Kingdom EH40/2005 Workplace exposure limits

NLD Nederland Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18

TLV-ACGIH ACGIH 2016



HI7040-1 - Zero Oxygen Solution, Component I

Revision nr.1 Dated 27/10/2016 Printed on 03/11/2016 Page n. 4 / 9

SECTION 8. Exposure controls/personal protection.

#### **SODIUM METABISULFITE**

Type Cou  VLA ESP  VLEP FRA  WEL GBF  OEL NLD	\ 5 R 5		STEL/15 mg/m3	min ppm				
VLEP FRA WEL GBF	5 A 5 R 5	3 ppm	mg/m3	ppm				
VLEP FRA WEL GBF	5 R 5 D 5							
WEL GBF	R 5							
	5							
OEL NLD								
TLV-ACGIH	5							
Predicted no-effect con	centration - P	NEC.						
Normal value in fresh water						1	mg/l	
Normal value in marine water						0,1	mg/l	
Normal value of STP microorganisms 75,4							mg/l	
Health - Derived no-effe	ect level - DNE	L / DMEL						
	Effects on co	onsumers.			Effects on workers			
Route of exposure		Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chroni c local	Chronic systemic
Oral.			VND	8,6 mg/kg bw/d				
Inhalation.			VND	66 mg/m3			VND	225 mg/m3

#### Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction. VND = hazard identified but no DNEL/PNEC available; NEA = no exposure expected; NPI = no hazard identified.

#### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

If the product may or must come into contact or react with acids, suitable technical and/or organisational measures should be taken to prevent the development of toxic and/or inflammable gases.

#### HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

## EYÉ PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

# RESPIRATORY PROTECTION

Use a type P filtering facemask (see standard EN 149) or equivalent device, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment.

## ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9. Physical and chemical properties.**

### 9.1. Information on basic physical and chemical properties.

Appearance solid powder Colour white Odour pungent Odour threshold. Not available. 4 - 4.5 pH, 17 g/L pH. Melting point / freezing point. Not available. Initial boiling point. Not applicable. Boiling range. Not available. Flash point. Not applicable. Not available. Evaporation rate Flammability (solid, gas) Not available. Lower inflammability limit. Not available





HI7040-1 - Zero Oxygen Solution, Component I

Revision nr.1 Dated 27/10/2016 Printed on 03/11/2016 Page n. 5 / 9

# SECTION 9. Physical and chemical properties. ..../>

Upper inflammability limit.

Lower explosive limit.

Upper explosive limit.

Vapour pressure.

Vapour density

Relative density.

Not available.

Not available.

Not available.

Not available.

1,480

Solubility soluble in water
Partition coefficient: n-octanol/water Not available.
Auto-ignition temperature. Not available.
Decomposition temperature. Not available.
Viscosity Not available.
Explosive properties Not available.
Oxidising properties Not available.
Not available.

9.2. Other information.

 Molecular weight.
 190,100

 Total solids (250°C / 482°F)
 100,00 %

 VOC (Directive 2010/75/EC):
 0

 VOC (volatile carbon):
 0

# **SECTION 10. Stability and reactivity.**

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions.

The powders are potentially explosive when mixed with air.

SODIUM METABISULFITE

Generates dangerous gases or fumes in contact with: acids. Exothermic reaction with: Oxidizing agents, nitrites, nitrates, Sulphides.

## 10.4. Conditions to avoid.

Avoid environmental dust build-up.

## 10.5. Incompatible materials.

Information not available.

## 10.6. Hazardous decomposition products.

Information not available.

# **SECTION 11. Toxicological information.**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

# 11.1. Information on toxicological effects.

SODIUM METABISULFITE

Eye irritation, Rabbit, Result: Eye irritation, Causes serious eye damage.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:

LC50 (Inhalation - mists / powders) of the mixture:

Not classified (no significant component).

LD50 (Oral) of the mixture: 1540,000 mg/kg

LD50 (Dermal) of the mixture: Not classified (no significant component).



# HI7040-1 - Zero Oxygen Solution, Component I

Revision nr.1 Dated 27/10/2016 Printed on 03/11/2016 Page n. 6 / 9

## SECTION 11. Toxicological information. .../>>

SODIUM METABISULFITE

LD50 (Oral). 1540 mg/kg Rat LD50 (Dermal). > 2000 mg/kg Rat

SKIN CORROSION / IRRITATION.

Does not meet the classification criteria for this hazard class.

SERIOUS EYE DAMAGE / IRRITATION.

Causes serious eye damage.

RESPIRATORY OR SKIN SENSITISATION.

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class.

# **SECTION 12. Ecological information.**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

## 12.1. Toxicity.

SODIUM METABISULFITE

EC50 - for Crustacea. 89 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants. 48 mg/l/72h Desmodesmus subspicatus

12.2. Persistence and degradability.

SODIUM METABISULFITE

Solubility in water. > 10000 mg/l

Biodegradability: Information not available.

12.3. Bioaccumulative potential.

SODIUM METABISULFITE

Partition coefficient: n-octanol/water. -3,7 Log Kow

12.4. Mobility in soil.

Information not available.

## 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

# 12.6. Other adverse effects.

Information not available.



HI7040-1 - Zero Oxygen Solution, Component I

Revision nr.1 Dated 27/10/2016 Printed on 03/11/2016 Page n. 7 / 9

# **SECTION 13. Disposal considerations.**

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

**CONTAMINATED PACKAGING** 

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information.**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

## 14.1. UN number.

Not applicable.

## 14.2. UN proper shipping name.

Not applicable.

## 14.3. Transport hazard class(es).

Not applicable.

# 14.4. Packing group.

Not applicable.

## 14.5. Environmental hazards.

Not applicable.

#### 14.6. Special precautions for user.

Not applicable.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

# **SECTION 15. Regulatory information.**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

None.

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.



# HI7040-1 - Zero Oxygen Solution, Component I

Revision nr.1 Dated 27/10/2016 Printed on 03/11/2016 Page n. 8 / 9

## SECTION 15. Regulatory information. />>

Substances subject to the Stockholm Convention:

None.

### Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (VwVwS 2005).

WGK 1: Low hazard to waters Substance listed in Annex 2.

#### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

## **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4
Eye Dam. 1
Eye Irrit. 2
H302
H318
H318
Causes serious eye damage, category 2
H319
Causes serious eye damage.
Causes serious eye damage.
Causes serious eye irritation.
EUH031
Contact with acids liberates toxic gas.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

## **GENERAL BIBLIOGRAPHY**

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament



HI7040-1 - Zero Oxygen Solution, Component I

Revision nr.1 Dated 27/10/2016 Printed on 03/11/2016 Page n. 9 / 9

## SECTION 16. Other information. .../>>

- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

## Changes to previous review:

The following sections were modified: 03.