

HI96704

Hydrazine Portable Photometer

- CAL Check™
 - Enables users to check validity of calibration
- BEPS
 - Alerts the user of low battery power that could adversely affect reading
- GLP Features
 - Meets Good Laboratory Practices

Hydrazine is a liquid chemical substance normally used in high pressure heating plants because of its properties as an oxygen inhibitor. It is added to avoid scaling and corrosion in the plant itself. Hydrazine reacts with dissolved oxygen to yield nitrogen and water; hydrazine thus has the advantage over the sulfite treatment because it does not produce any dissolved solids in the boiled water. Hydrazine is also used in tanks because it controls the growth of bacteria. Other hydrazine uses include:

- Oxygen scavenger for water boiler feed and heating systems to prevent corrosion damage
- Energy source in fuel elements
- Reducing agent for the recovery of metals (copper, nickel and others)
- Intermediate in insecticides, herbicides, explosives, plant growth regulators, pharmaceuticals, dyes, flame-retardants, polymerization catalysts and other chemical products
- Component of photo development

The HI96704 meter measures the hydrazine content in water samples. The method is an adaptation of the ASTM Manual of Water and Environmental Technology, method D1385-88 for natural and treated water. The reaction between hydrazine and liquid reagent causes a yellow tint in the sample.



Specifications	HI96704 Hydrazine
Range	0 to 400 µg/L (ppb)
Resolution	1 µg/L
Accuracy @ 25°C (77°F)	±3% of full scale
Light Source	light emitting diode
Light Detector	silicon photocell with narrow band interference filter @ 466 nm
Power Supply	9V battery
Auto-off	after ten minutes of non-use in measurement mode; after one hour of non-use in calibration mode; with last reading reminder
Environment	0 to 50°C (32 to 122°F); RH max 95% non-condensing
Dimensions	193 x 104 x 69 mm (7.6 x 4.1 x 2.7")
Weight	360 g (12.7 oz.)
Method	adaptation of the ASTM Manual of Water and Environmental Technology, method D1385-88 for natural and treated water
Ordering Information	<p>HI96704 is supplied with sample cuvettes (2) with caps, 9V battery, instrument quality certificate and instruction manual. CAL Check™ standards and testing reagents sold separately</p> <p>HI96704C includes photometer, CAL Check™ standards, sample cuvettes (2) with caps, 9V battery, cuvette wiping cloth, instrument quality certificate, instruction manual and rigid carrying case. Reagents sold separately</p>
Reagents and Standards	<p>HI96704-11 CAL Check™ standard cuvettes</p> <p>HI93704-01 reagents for 100 tests</p> <p>HI93704-03 reagents for 300 tests</p>

Standard reagents begin on page 10.70; CAL Check™ standard reagents begin on page 10.71