


TM-201 TM-202



Display

- 3 1/2 digits LCD with maximum reading 2000
- Overload indication: OL
- Low battery indication: “”

Features

- According to JISC 1609: 1993 and CNS 5119 general A class specifications
- Spectral response close to CIE luminous spectral efficiency
- Measuring all visible light source
- Length of wire for light sensor: approx. 1.5M
- Cosine angular corrected

TM-201	Data hold Max hold Zero adjustment	Sensor: silicon photo diode and filter Dimension: 130x56x38mm (LxWxH) Sensor size: 80x56x25mm (LxWxH) Weight: 250g
TM-202	Data hold DC analog output Max/Min hold Zero adjustment	

Specifications


	TM-201	TM-202
Measuring range	200, 2000, 20000, 200000 Lux 20, 200, 2000, 20000 Foot-candle	20, 200, 2000, 20000, 200000 Lux 20, 200, 2000, 20000 Foot-candle
Accuracy	±3% (calibrated to standard incandescent lamp 2856°K) ±8% (other visible light source)	±3% (calibrated to standard incandescent lamp 2856°K) ±6% (other visible light source)
Angle deviation from cosine characteristics	10° 30° 50° 60° 80°	±0.5% ±2% ±3% ±6% ±25%

Applications include :warehouses, factories, office buildings, restaurants,schools, library, hospitals, photographic, video, parking garages, museums, art galleries, stadiums, building security.

TM-720 Mini Pocket Light Meter (Auto-Ranging)



Display

- 3 3/4 digits LCD with maximum reading 3999
- Low battery indication: “”
- Overload indication: OL

Features

- According to JISC 1609:1993 and CNS 5119 general A class specifications
- Spectral response close to CIE luminous spectral efficiency
- Silicon photo diode and filter
- Max/Min/AVG hold
- Auto power off with disable function
- Auto ranging
- Cosine angular corrected
- Measuring all visible light sources
- Real zero function
- Data hold

Specifications

Accuracy	±3% ±3 Lux (0~500 Lux) ±3% (up 501 Lux) (calibrated to standard incandescent lamp 2856°K) ±8%(other visible light source)	Measuring range	400, 4000, 40000, 400000 Lux 40, 400, 4000, 40000 foot-candle
		Meter size: 133 x 48 x 23mm (L x W x H) Power: 2 batteries 1.5V AAA Weight: 80g (including battery)	