

# Coating Thickness Gauge (Functional Type)



**Model:** CM-8829 CM-8829S CM-8829H

## Applications

Coating thickness gauge is a kind of portable measuring instrument, can take fast, intact, precise measurement of coating thickness. It can not only be used in engineering field, laboratories, but also meet the demand of multiple measuring by using different probes. It is used widely in manufacturing, metal processing industry, chemical industry, commodity inspection field, etc. As an essential instrument in material protection industry.



## Principles

Principles	Applications	Examples
F Type Magnetic Induction (Iron Base)	Measure the thickness of non-magnetic materials on magnetic materials	Galvanizing layer, lacquer layer, porcelain enamel layer, phosphide layer, copper tile, aluminium tile, some alloy tile, paper etc
NF Type Eddy Current (Aluminium Base)	Measure the thickness of non-conductive coatings on non-magnetic metals	Anodizing, varnish, paint, enamel, plastic coatings, powder, etc. Applied to aluminum, brass, non-magnetic stainless steel, etc



## Features

- \* Two principles: Magnetic Induction and Eddy Current.
- \* Two measurement mode: Single and Continuous.
- \* The CM-8829H is a large range meter, range 0~12mm.
- \* Metric/imperial system selectable.
- \* Manual or automatic power off.
- \* Automatic memory of calibration value, and automatic recognize the substrate.
- \* Operation process have buzzing reminder.
- \* Integral Type have better stability and repeatability.
- \* Separate Type can provide several types of probes, measure can be more flexibility.
- \* Use RS-232 data output to connect with PC.
- \* Provide Bluetooth data output choice.

## Specifications

Model	Integral	CM-8829FN	CM-8829N	CM-8829F	—
	Separate	CM-8829FNS	CM-8829NS	CM-8829FS	CM-8829H
Principle	F Magnetic Induction	✓	—	✓	✓
	NF Type Eddy Current	✓	✓	—	✓
Range		0~1250μm / 0~50mil			0~12mm / 0~480mil
Resolution		0.1μm / 1μm			0.01mm / 0.1mm
Accuracy		±1~3%n or ±2.5μm			±1~3%n or ±0.2mm
Min. Radius Workpiece		F Type: convex 1.5 mm / concave 25 mm NF Type: convex 3 mm / concave 50 mm			convex 20 mm / concave 50 mm
Min. Measuring Area		6 mm			16 mm
Min. Sample Thickness		0.3 mm			0.3 mm
Metric / Imperial		Convertible			
Battery Indicator		Low Battery Indicator			
Automatic Power Off		✓			
Operating Conditions	Temperature	0~50°C			
	Humidity	< 80%RH			
Power Supply		4x1.5V AAA (UM-4) Battery			
Dimensions		126x65x27mm			
Weight (Not Including Batteries)		115g			210g

Standard Accessories	Main Unit	✓	✓	✓	✓
	Probe (F Type)	✓	—	✓	—
	Probe (NF Type)	✓	✓	—	—
	Large Range Probe (F)	—	—	—	✓
	Calibration Base (F)	✓	—	✓	✓
	Calibration Base (NF)	✓	✓	—	—
	Calibration Foils	1 set, 4 pieces			
	Carrying Case	B04			
	Operation Manual	✓			
Optional Accessories		RS-232C Data Cable with Software			
		Bluetooth Data Adapter with Software			