


Mobile Wireless Multi-Gas Team Warning System




The mSquad System is a quickly-deployable set of mobile multi-gas meters that communicate wirelessly to a Squad leader up to 0.8 km (0.5 miles) distant. The system is ideal for Hazmat Response, firefighters, temporary venue protection, etc. An mSquad consists of one Head monitor (MP400H) and up to 7 Soldier monitors (MP400S) that communicate with each other. Each 4- or 5-gas monitor has options for a full range of sensors for toxic gases, oxygen (O₂), combustibles (LEL) and carbon dioxide (CO₂). The MP400S can also have a PID for volatile organic compounds (VOCS). In addition to high gas concentration alarms, all Squad units receive any Man-Down alarms to notify them remotely of a worker in distress. All the Squad monitors are Class I Division I certified to operate in hazardous zones. The entire mSquad is mobile, running on batteries for up to 12 hours. The MP400S and MP400H have rugged construction and easy-to-learn 2-button operation.

Features, Functions and Benefits

- Remote, wireless real-time readings and alarms including Man-down
- Up to 8 remote 4- or 5-gas monitors
- Up to 0.8 km (0.5 miles) distance to Squad Head
- All mSquad units alarm if any one unit has an alarm condition
- Mobile system operation
- 12-hour continuous operation on single Li-ion battery charge.
- USB Micro cable for battery charging and direct PC communication
- Wide selection of sensor types



MP400S and MP400H Specifications

Size	5.7 x 3.3 x 1.7 in (140 x 84 x 42 mm) w/o Antenna
Weight	15.5 oz (435 g)
Sensors	Interchangeable and field-replceable: PID for VOCs (MP400S only), EC for Toxic & O ₂ , Pellistor for LEL, and NDIR for LEL, Vol% & CO ₂
Response time (t90)	<ul style="list-style-type: none"> • 15 s (LEL/CO/H₂S/O₂) MP400S • 20 s (LEL/CO/H₂S/O₂) MP400H • Others vary up to 120 s
Sampling	MP400S - Internal pump; MP400H - Diffusion
Battery	12 hr (depending on sensors and pump installed)
Direct Readout	<ul style="list-style-type: none"> • Real-time reading of gas concentration • PID measurement gas and correction factor, • Battery status • STEL, TWA, peak and minimum values • Man-Down alarm on/off
Display	128 x 128 graphical LCD, 1.77 x 1.73 in (45 x 44 mm), with LED backlight and auto "flip" screen
Range	0.8 km (1/2 mile) between MP400H and MP400S
Frequency	ISM band (902-928 MHz) FCC Part 15 approved
Calibration	Zero and span calibration. Single or multiple sensor simultaneous calibration settings
Monitors	Up to 8 per mSquad (1 MP400H plus 7 MP400S)
Alarms	<ul style="list-style-type: none"> • Audible (95 dB @ 30 cm) • Visual (flashing bright red LEDs) • Vibration • On-screen indication of alarm conditions • Man-Down alarm with pre-alarm
Wireless Alarm Notification	Alarm on any monitor sent to all others in mSquad for 5 seconds, then remains on at MP400H
Datalogging	Continuous datalogging (6 months for 4 sensors at 1-minute intervals, 24 hours/day and 7 days/week)
Direct PC Comm and Charging	USB cable for charging, data download, instrument setup and firmware upgrades on PC or 100-240V AC charger, or CaliCase.
Temperature	-4° to 122°F (-20° to 50°C)
Humidity	0% to 95% Relative humidity (non-condensing)
IP Rating	IP-65 MP400S (pump); IP-67 MP400H (diffusion)
Safety Certifications	 Class I, Div 1, Group ABCD T4, -20°C ≤ T _{amb} ≤ +50°C IECEX Ex ia IIC T4 Ga ATEX II 1G Ex ia IIC T4 Ga (pending) CE European Conformity (pending)
EMC/RFI	EMC directive: 2014/30/EU
Warranty	<ul style="list-style-type: none"> • 2 Years on instruments • 2 Years on sensors for pellister LEL, and O₂, CO, H₂S, SO₂, HCN, NO, NO₂, and PH₃ EC sensors • 1 Year on other sensors

Sensor Options

Sensor	Range	Resolution
PID	0-2000 ppm	0.1 ppm
Oxygen (O ₂)	0-30%Vol	0.1%Vol
Combustibles (LEL%)	0-100%LEL	1%LEL
Hydrocarbons (Vol%)	0-100%Vol	0.1%Vol
CO ₂ (Carbon Dioxide)	0-50000 ppm	100 ppm
CO (Carbon Monoxide)	0-1000 ppm	1 ppm
H ₂ S (Hydrogen Sulfide)	0-100 ppm	0.1 ppm
	0-1000 ppm	1 ppm
CO + H ₂ S	CO 0-500 ppm	1 ppm
	H ₂ S 0-200 ppm	0.1 ppm
SO ₂ + H ₂ S	SO ₂ 0-20 ppm	0.1 ppm
	H ₂ S 0-100 ppm	0.1 ppm
NH ₃ (Ammonia)	0-100 ppm	1 ppm
Cl ₂ (Chlorine)	0-50 ppm	0.1 ppm
ClO ₂ (Chlorine Dioxide)	0-1 ppm	0.01 ppm
H ₂ (Hydrogen)	0-1000 ppm	10 ppm
HCl (Hydrogen Chloride)	0-15 ppm	0.1 ppm
HCN (Hydrogen Cyanide)	0-100 ppm	1 ppm
NO (Nitric Oxide)	0-250 ppm	1 ppm
NO ₂ (Nitrogen Dioxide)	0-20 ppm	0.1 ppm
PH ₃ (Phosphine)	0-20 ppm	0.01 ppm
SO ₂ (Sulfur Dioxide)	0-20 ppm	0.1 ppm
ETO (Ethylene Oxide)	0-100 ppm	0.1 ppm
CH ₃ SH (Methyl Mercaptan)	0-10 ppm	0.1 ppm

Distributed By:



* Due to ongoing research and product improvement, specifications are subject to change without notice *