



HT-1805

Four in one gas detecto : เครื่องตรวจจับแก๊สหลากหลายพารามิเตอร์

It can be used in mining,metallurgy security ring,petrochemical, power telecommunications,municipal and other occasions.

Specification

Vibration-proof enclosure
2in color display
Detection of gas:H2s/CO/O2(%Volume ratio)/Combustible gas (site selection)
Measurement range:0-100ppm(H2S)/0-500ppm(CO)0-25%(O2)
0-100%LEL(Combustible gases)
Rechargeable Battery
Visual,auditory alarm and buzzer alarm
Automatic or mobile phone open, red flashing, vibration
Alarm values can be set
Full function self-test
Size:136mm×68mm×34mm
Weight:250g

PM2.5 Detector

This product is featured by high precision, stable performance, easy operation, and convenient carrying; it is suitable for household indoor, office, vehicle and natural environment.



HT-403

Specification

Measuring range	0~999ug/m3
Resolution	1ug/ m3
Accuracy	±10ug/ m3 (0~100ug/ m3) ; ±10%(100~500ug/ m3)
Refresh time	about 1 second
Automatic shutdown	30 minutes
Use time	about 2 hours
Charging time	about 3.5 hours
Operating temperature	0 ~ 50 C
Working humidity	0 ~ 90% RH
Power supply	Built-in 3.7V lithium battery
Size	74mm × 71mm × 27mm
Weight	76g