



[Single or Multi]

K-600

Gas Detector with **Built in Pump**

Technical Parameters

Gas sampling method: Pumping

Alarm methods: sound, light, vibration, curve display

Working Temperature: -20°C-50°C

Power: 3.7V 3600mA rechargeable lithium battery

Charging time: 4-6 hours

Display: 2.4 inch colored LCD display

Operating time: working continuously for at least 10 hours

Explosion proof: Exib IIC T4 Gb



Size: 174x68x47mm

www.bosean.com Q

K-600 Gas detector with Built in Pump (Single or Multi)

K-600 portable multi-gas detector with built-in pump is a new intelligent gas detector, which adopts an advanced integrated circuit, with standard intelligent level design technology, and proprietary digital analog hybrid communication technology. The detector is of excellent sensitivity and repeatability, which makes it very easy to use and maintain. Thus greatly meets the safety requirements of industrial sites with high reliability. The detector is made of high-strength engineering plastics, compound nonslip rubber, which is of high strength and good hand feeling. what's more, the detector is water-proof, dust-proof and explosion-proof.

It is widely used in petroleum, chemical, environmental, metallurgy, refining, gas transmission and distribution, biochemical medicine, agricultural and other industries.



Industrial

sensor



methods















(2) HOTLINE: +86 15639790605

Can detect more than 30 kinds of gases, can customize flexibly according to users' need (detect 5 different gases in one unit). normally detect Ex, O2,H2S,CO gases.

¦¦ Range

EX: 0~100%LEL O₂: 0~30%VOL H₂S: 0~100PPM CO: 0~1000PPM

Resolution

EX: 1%LEL O₂: 0.1%VOL H₂S: 1PPM CO: 1PPM









Q 10th Floor, Building 10, Enterprise Park, No. 228, West Fourth Ring, High-tech Zone, Zhengzhou City