




K-100


Single Gas Detector

 Exib IIC T4 Gb

SIL FC RoHS CE   

Technical Parameters

Alarm type:	sound, light, vibration curve display	Sampling method:	Natural Diffusion
T(90):	<30S	T&H:	-10°C ~ 55°C, <95%RH
Charging time:	6~8 hours	Sensor life:	2 years
Working time:	≲8 hours	Display:	1.7 inch colored LCD
Dimensions:	124 × 60 × 32mm 130g	Precision level:	IP65











Portable Single Gas Detector

K-100 portable gas detector, using imported sensors and microcontrol technology, fast response, high accuracy, good stability and repeatability, the performance of the gas detector is industry leading level, simple operation.

Industrial sensor, colored screen, perfectly display various technical indicators and gas concentration value, with dual screen switching function to view historical alarm data on the screen and data storage function.

Rubber - coated industrial non - slip design shell, small size and easy to carry. Suitable for explosion-proof, poisonous gas leakage emergency, underground pipeline, mine, metallurgy, power plant, chemical, tunnel, tunnel and other places, effectively prevent the occurrence of poisoning accident, ensure the safety of the staff and production equipment from damage.

Product Features

-  ppm、mg/m3 switch
-  Four alarm methods
-  T&H display
-  Double background switching
-  Support TWA/STEL
-  Two gases can be customized



Technical Data

Gas	Range	Unit	Resolution
Ex	1-100	%LEL	1%LEL
H2S	0-100	PPM	1PPM
CO	0-1000	PPM	1PPM
O2	0.0-30.0	%VOL	0.1%VOL



+86 371-86533226

sales@bosean.com

Block 10. Yida New Park No. 16 JinZhan Road, High-Tech zone, Zhengzhou, Henan Province.