



- PDF Format



➤ **Flaw Detector**

▶ [Ultrasonic Flaw Detector](#)

▶ [Magnetic Flaw Detector](#)

➤ [Surface Roughness Tester](#)



Description

Magnetic Defect Detector **Leeb610/Le**

Your name*:

Your E-mail*:

Got a question?*:

Send



Function & Feature:

- I With LED light, which have a longer service life and can be changed conveniently.
- I Small volume, light weight, large lifting force, and adaptable joint. Fit to be used for the detecting of the weld bead, steel pipe, I AC and DC.
- I Lithium Battery, Charging time is about 3 to 5 hours, then can be used for about 6-8 hours continuously.
- I This model has applied for national patent technology , prohibit other company to imitate.

Application Fields:

I Fit to be used for the detecting of Oil field, Boat making, Car making, Coal mine, Machine, Medicine, Airplane making and inte
I Fit to the detecting for the surface defecting caused by Forge, Quenching,Welding, Fatigue etc.

Technical Specification:

	Leeb610	Leeb610A
Power supply mode	alternating current	alternating current-direct current
Input votage	220V±10%, 50-60Hz	
Working power	alternating current 2A, direct current1.8A	
Probe limits	20-200mm	
sensitivity	Type A specimens show clear	
Elevating weight	alternating current(plane)8kg; direct current more than 30kg	
LED lighting	3W	
Work period	2 minutes to start up and 2 minutes to stop	
electric cable	5.5m	
Work temperature	-10-50℃	
Overall dimension	190*248*546mm	
weight	2.9kg	
Standard configuration	Main machine 、 Input electric cable, paste, electroscope, lithium battery , charger.	