

Thermal Anemometer PCE-009



Accurate thermal anemometer to measure air temperature and velocity with calculation of volume of air current and RS-232 interface for data transfer to a computer, software and cable is included

This thermal anemometer has a good relation between price and quality and it combines accuracy and versatility with the ability to transfer data directly to a computer. This air thermal anemometer forms a part of a professional's basic equipment to regulate and test ventilation systems. This thermal anemometer is also used in research and development projects within institutions. Its fine 8 mm / .3 in point makes it possible to use in areas where there is limited space to measure, such as cooling systems. When a surface area is input into the thermal anemometer it will calculate the volume of air current in m³/min. In this way, the capacity of a ventilation can be controlled and it can be used for air conditioning and refrigeration systems. It should be taken into account that when measuring air flow, various measurements should be taken and the average used to represent the air flow reading.

- Measures air velocity and temperature
- ▶ Calculates volume of air current as well as average volume of air current
- ▶ Can be used for low air velocity
- ▶ Different units of measurement: m/s, km/h, ft/min, knots, miles/h
- ▶ Large LCD
- ▶ Easy to use
- ▶ Shows minimum and maximum value
- ▶ Save function for minimum and maximum values
- ▶ Auto shut-off function to protect battery life
- ▶ Has an RS-232 interface for data transfers to a computer
- ▶ Comes with a telescopic sensor, batteries, carrying case, software, RS-232 cable and user's manual

Specifications

Measurement range with corresponding unit:	
- m/s	0.2 ... 20.0
- °C / °F	0.0 ... 50.0 / 32 ... 122°F (sensor)
Calculation of volume of air current:	0 ... 36,000
- m ³ /min (CCM)	
Resolution	
- Air velocity	0.1m/s (for remaining units, up to ft/min = 1.0)
- Air temperature	0.1°C / 0.18°F
- Volume of air current (CCM)	0.001 to 1m ³ /min (depending on reading)
Accuracy	±1% (of measurement range) or ±5% of the corresponding value
- Air velocity	
- Air temperature	±0.8°C / 1.4°F
- Volume of air current (CCM)	Calculated value
Measuring quote	From 2 sec. to 9 hours
Internal memory	16.000 values
	- Telescopic thermistor
	- Hot wire sensor
	- Contracted length 280 mm / 11 in
Thermal sensor	- Extended length 940 mm / 37 in
	- Maximum diameter 12 mm / .5 in
	- Minimum diameter 8 mm / .3 in (at the leading end)
Interface	RS-232
	- Included, compatible with Windows 95, 98, 2000, XP, for data transfer
Software / RS-232 cable	- Data can also be exported to MS Excel
Display	Large 58 x 34 mm / 2.3 x 1.4 in LCD
Operating conditions	Device: 0°C ... 40°C / 32 ... 104°F <80% r.h. Thermal sensor: 0°C ... 50°C / 32 ... 122°F <80% r.h.
Power	4 batteries (1.5V) (or by way of an optional mains adaptor of 9V)
Auto shut-off	Yes, 5 minutes to protect battery power
	Device: 203 x 76 x 38 mm / 8 x 3 x 1.5 in
Dimensions	Thermal sensor: 8 mm / .3 in diameter x 940 mm / 37 in maximum extended length (only 280 mm / 11 in when contracted)
Enclosure	ABS plastic
Weight	515 g / 1.1 lbs

More information

Manual



More product info



Similar products



Subject to change