

# TES-1336A Datalogging Light Meter (RS-232)



## FEATURES

- Spectrum of photo sensor meets C.I.E. photopic curve V(λ)
- 16000 Records Data logging capacity
- RS - 232 interface (software included)
- Measurement of luminous intensity (PC Software)



## SPECIFICATION

Measuring range	20/200/2000/20000 Lux, 20/200/2000/20000 Fc
Luminous intensity (cd)	Intensity = illuminance x (length) 2
Length	feet (Fc) meter (Lux)
Resolution	0.01 Lux
Accuracy	± ( 3% rdg + 5dgts ) (calibrated to standard incandescent lamp, 2856 K)
Overrange display	OL
Record (Data logging)	16000 Point Data logger
Sensor	Silicon photo diode
Sensor lead length	150cm (approx)
Sensor probe	100(L) x 60(W) x 27(H) mm
Power source	One 9V battery
Battery life	50hrs (approx)
Operating Storage Condition	0 °C ~ 40 °C ( 32 °F~104 °F ) below 80% RH - 10 °C ~ 60 °C ( 14 °F~140 °F ) below 70% RH
Dimensions	146(L) x 70(W) x 39(H) mm
Weight	300g (approx)
Accessories	Carrying case, 9V battery, instruction manual, Software, RS - 232 cable, 9 Pin to 25 Pin gender changer screwdriver.



[www.A-A.co.kr](http://www.A-A.co.kr)

Tel:031-704-2401 Fax:031-704-2421 E-mail:aaa@a-a.co.kr

전기전자 반도체 대기환경 물리물성 수질 이화학 비파괴 전문회사